



PIN NO	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
SEGMENT	COM	□	B-C	NC	NC	NC	NC	4DP	3E	3D	3C	3DP	2E	2D	2C	2DP	1E	1D	1C	1B
PIN NO	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
SEGMENT	1A	1F	1G	2B	2A	2F	2G	COL	3B	3A	3F	3G	NC	NC	NC	NC	NC	NC	NC	COM

1. ALL DIMENSIONS ARE IN mm WITH ± 0.20 TOLERANCE UNLESS OTHERWISE SPECIFIED.
2. VIEWING ANGLE: 6:00 O'CLOCK.
3. VIEWING MODE: POSITIVE, REFLECTIVE
4. DISPLAY TYPE : TN
5. CONNECTION: PIN
6. FLUID SPECIFICATION:
 - DRIVING VOLTAGE: 3.0--5.0V
 - MULTIPIXEL LEVEL: STATIC
 - OPERATING TEMP. : -20°C -- +70°C
 - STORAGE TEMP. : -30°C -- +80°C


厦门精显电子有限公司
 XIAMEN PRECISE DISPLAY CO., LTD.

客户确认:		单位: mm	
绘图: 姚晓虹	审核: 	绘图编号: GYTN0587	日期: 2004.07.16
批准:	客户编号: PD-G0578P	图纸版号: 01	页数: 1/3